

# solving cleaning problems



*The Action Line*

LIQUID PROPANE, ECONOMICAL AND CLEAN BURNING, fuels the Models 2121-P and 3151-PT. A 45 pound L.P. tank plus ball bearing pneumatic wheels allows these units to be easily moved from one cleaning problem to the next.

Imagine several of the design characteristics of Alkota Cleaning Systems famed "Cleaning Crew" in a L.P. gas fired unit. Both units are engineered with modern pumps where the crankcase is filled with oil and the plungers are of ceramic or rugged useage and long life. Features such as precise chemical metering, stainless steel float tanks, heavy steel construction, and rotary electrical switches provide quality, dependability, and operator convenience.

Designed for useage where oil fumes may be a problem, these liquid propane washers are ideal for restaurants, hospitals, fast food chains, and pharmaceuticals.



Manufactures of quality · hot and cold pressure washers · steam cleaners and hot water heaters



CLEANING SYSTEMS, INC.

Box 158 • Alcester, South Dakota 57001 • Phone 605-934-2222



## CLEANING SYSTEMS INC.

MODEL	2121 P	3151 P-T
Capacity*	2.1 GPM	3 GPM
Pressure*	1200 PSI	1500 PSI
Pump	Duplex, Oil Bath	Triplex, Oil Bath
Motor**	2 H.P., 115 V., 1 PH.	4 H.P., 220 V., 1 PH.
Coil*** (Steel Pipe)	126', 5/8" I.D. Schedule 40	126', 5/8" I.D. Schedule 40
Burner, Gas Natural Aspirating, Nat. or L.P. Gas	200,000 BTU	200,000 BTU
Gas Consumption	Nat. - 191 Cu. Ft. per Hr. L.P. - 2.2 GPH	Nat. - 191 Cu. Ft. per Hr. L.P. - 2.2 GPH
Wand	Open - Std. Trigger - Opt.	Trigger
Hose	3/8" x 50'	3/8" x 50'
Chemical	Precise Metered	Precise Metered
Float Tank Stainless Steel	Standard	Standard
Temperature Control	Optional	Optional
Steam Capacity (Optional)	60 GPH	90 GPH
Wheels	10" Ball Bearing Pneumatic	10" Ball Bearing Pneumatic
Dimensions	34" L., 27 1/2" W., 42" H.	34" L., 27 1/2" W., 42" H.
w/Bottle & Reg.	49" L., 27 1/2" W., 42" H.	49" L., 27 1/2" W., 42" H.
Weight	400 lbs.	420 lbs.
Bottle Pack 45 lb. Bottle w/Regulator	Optional	Optional

\*Gallonage and Pressure may vary + or - 5% Due to Manufacturing Tolerances in Components.

\*\*Special Voltages upon Request. Gallonages and Pressures may be less on 3 Phase Current.

\*\*\*ASTM A-53 Steel Pipe, Spiral Wound, Cold Water Wrap Design, Removable.

### ENGLISH TO METRIC CONVERSION CHART

1 gallon/minute  
= 3.78 liters/minute

1 foot = .3048 meters

1 horsepower = .746 kilowatts

1 inch = 2.54 centimeters

100 PSI = 7.03 Kg/cm<sup>2</sup>

1 pound = .45359 kilograms

Distributed by:

**ALKOTA CLEANING SYSTEMS, INC.**

ALCESTER, SOUTH DAKOTA 57001

PHONE 605/934-2222

PRINTED IN USA

MEMBER OF  
**CEMA**  
CLEANING EQUIPMENT  
MANUFACTURERS ASSOCIATION

FORM LPP 8/89